


ABM-IA-M3 - SW5 Abstandsbolzen




Merkmale

- 6-kant Abstandsbolzen mit M3 Innen-/Außengewinde
- Schlüsselweite (SW) 5
- Außengewinde mit Hinterstich nach DIN76
(kein Buchstabe „H“ in der Art.-Nr. bedeutet "ohne Hinterstich")
- Material: Messing vernickelt

Abmessungen

► Einheit = mm



Art.-Nr.	L (mm)	B (mm)	C (mm)
104 13 04 H	4,0	6,0	2,0
104 13 04 HB8	4,0	8,0	2,0
104 13 05 HB4	5,0	4,0	2,5
104 13 05 HB6	5,0	6,0	2,5
104 13 05 HB8	5,0	8,0	2,5
104 13 05 H	5,0	8,0	2,5
104 13 06 HB4	6,0	4,0	4,0
104 13 06 HB6	6,0	6,0	4,0
104 13 06	6,0	8,0	4,0
104 13 06 H	6,0	8,0	4,0
104 13 06 B12	6,0	12,0	4,0
104 13 07	7,0	8,0	4,0
104 13 08 HB6	8,0	6,0	5,0
104 13 08	8,0	8,0	5,0
104 13 08 H	8,0	8,0	5,0
104 13 08,5	8,5	6,0	5,0
104 13 09 H	9,0	8,0	5,0
104 13 10	10,0	6,0	5,0
104 13 11	11,0	8,0	6,0
104 13 11H	11,0	8,0	6,0
104 13 12 HB6	12,0	6,0	8,0
104 13 12 H	12,0	8,0	8,0
104 13 13 H	13,0	8,0	8,0
104 13 13,5 HB6	13,5	6,0	8,0
104 13 13,5 H	13,5	8,0	8,0
104 13 14 H	14,0	8,0	7,0
104 13 15 HB4	15,0	4,0	10,0

Art.-Nr.	L (mm)	B (mm)	C (mm)
104 13 15 HB6	15,0	6,0	7,0
104 13 15 H	15,0	8,0	10,0
104 13 15 HB10	15,0	10,0	10,0
104 13 16 HB6	16,0	6,0	10,0
104 13 17 H	17,0	8,0	10,0
104 13 17 HB10	17,0	10,0	10,0
104 13 18	18,0	8,0	10,0
104 13 20 HB6	20,0	6,0	10,0
104 13 20	20,0	8,0	10,0
104 13 20 H	20,0	8,0	10,0
104 13 25	25,0	6,0	10,0
104 13 25 H	25,0	10,0	10,0
104 13 25 HB8	25,0	8,0	10,0
104 13 29 HB6	29,0	6,0	7,0
104 13 30 HB6	30,0	6,0	10,0
104 13 30 H	30,0	8,0	10,0
104 13 30 HB10	30,0	10,0	10,0
104 13 35 H	35,0	6,0	10,0
104 13 36	36,0	10,0	10,0
104 13 36 HB10	36,0	10,0	10,0
104 13 37 HB10	37,0	10,0	10,0
104 13 38 H	38,0	8,0	10,0
104 13 40 HB6	40,0	6,0	10,0
104 13 40	40,0	8,0	10,0
104 13 45 H	45,0	10,0	10,0
104 13 50 H	50,0	10,0	10,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0



THORA
elektronik

www.thora.com