

ABS-IA-M3 - SW5,5 Abstandsbolzen




Merkmale

- 6-kant Abstandsbolzen mit M3 Innen-/Außengewinde
- Schlüsselweite (SW) 5,5
- Außengewinde mit Hinterstich nach DIN76
(kein Buchstabe "H" in der Art.-Nr. bedeutet "ohne Hinterstich")
- Material: Stahl verzinkt

Abmessungen

► Einheit = mm



Art.-Nr.	L (mm)	B (mm)	C (mm)
106 03 04 H	4,0	6,0	2,5
106 03 05 HB3,5	5,0	3,5	3,0
106 03 05 HB4	5,0	4,0	3,0
106 03 05 B5	5,0	5,0	3,0
106 03 05 HB5	5,0	5,0	3,0
106 03 05 H	5,0	6,0	3,0
106 03 05 HB12	5,0	12,0	3,0
106 03 06 H	6,0	6,0	4,0
106 03 07 HB4	7,0	4,0	4,0
106 03 07 H	7,0	6,0	4,0
106 03 07,5 H	7,5	6,0	4,0
106 03 08 H	8,0	6,0	5,0
106 03 08 HB4	8,0	4,0	5,0
106 03 08,5 HB3,5	8,5	3,5	5,0
106 03 09 HB4	9,0	4,0	6,0
106 03 09 H	9,0	6,0	5,0
106 03 10 HB3,5	10,0	3,5	6,0
106 03 10 H	10,0	6,0	6,0
106 03 10 HB8	10,0	8,0	6,0
106 03 11 H	11,0	6,0	6,0
106 03 11,5H	11,5	6,0	6,0
106 03 12 H	12,0	6,0	6,0
106 03 12,5 HB6	12,5	6,0	6,0
106 03 13 H	13,0	6,0	6,0
106 03 13,5 H	13,5	6,0	6,0
106 03 14 H	14,0	6,0	6,0
106 03 15 HB3	15,0	3,0	6,0
106 03 15 HB3,5	15,0	3,5	6,0
106 03 15 H	15,0	6,0	6,0
106 03 16 HB3,5	16,0	3,5	6,0
106 03 16 H	16,0	6,0	6,0
106 03 16,5 HB5	16,5	5,0	6,0
106 03 16,5 H	16,5	6,0	6,0
106 03 17 HB3	17,0	3,0	6,0
106 03 17 HB3,5	17,0	3,5	6,0
106 03 17 HB4	17,0	4,0	6,0
106 03 17 H	17,0	6,0	7,0
106 03 17 HB10	17,0	10,0	6,0
106 03 17,5 H	17,5	6,0	6,0
106 03 18 H	18,0	6,0	6,0
106 03 18,5 H	18,5	6,0	6,0
106 03 20 H	20,0	6,0	6,0
106 03 21 H	21,0	6,0	6,0
106 03 22 H	22,0	6,0	6,0

Art.-Nr.	L (mm)	B (mm)	C (mm)
106 03 23 H	23,0	6,0	7,0
106 03 24 H	24,0	6,0	6,0
106 03 25 H	25,0	6,0	6,0
106 03 26 H	26,0	6,0	6,0
106 03 27 H	27,0	6,0	6,0
106 03 28 H	28,0	6,0	6,0
106 03 29 H	29,0	6,0	6,0
106 03 30 H	30,0	6,0	6,0
106 03 30 HB10	30,0	10,0	10,0
106 03 30 HB15	30,0	15,0	6,0
106 03 31 H	31,0	6,0	10,0
106 03 31,5 H	31,5	6,0	7,0
106 03 32 H	32,0	6,0	6,0
106 03 32,7 HB6	32,7	6,0	6,0
106 03 33 H	33,0	6,0	6,0
106 03 34 H	34,0	6,0	6,0
106 03 35 H	35,0	6,0	7,0
106 03 36 H	36,0	6,0	6,0
106 03 36 HB16	36,0	16,0	6,0
106 03 37 HB4	37,0	4,0	7,0
106 03 38 H	38,0	6,0	6,0
106 03 39 H	39,0	6,0	6,0
106 03 40 H	40,0	6,0	7,0
106 03 43 H	43,0	6,0	6,0
106 03 44 HB6	44,0	6,0	7,0
106 03 45 H	45,0	6,0	6,0
106 03 47 H	47,0	6,0	6,0
106 03 48 H	48,0	6,0	6,0
106 03 48 HB16	48,0	16,0	6,0
106 03 48,5 H	48,5	6,0	6,0
106 03 50 H	50,0	6,0	6,0
106 03 53 H	53,0	6,0	6,0
106 03 55 H	55,0	6,0	6,0
106 03 55 HB11	55,0	11,0	6,0
106 03 58 H	58,0	6,0	6,0
106 03 60 H	60,0	6,0	6,0
106 03 70 H	70,0	6,0	6,0
106 03 75 H	75,0	6,0	6,0
106 03 80 H	80,0	6,0	6,0
106 03 85 H	85,0	6,0	6,0
106 03 88 H	88,0	6,0	6,0
106 03 90 H	90,0	6,0	6,0
106 03 100 H	100,0	6,0	6,0
106 03 120 H	120,0	6,0	6,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0



THORA
elektronik

www.thora.com