


ABM-IA-M3 - SW5,5 Abstandsbolzen




Merkmale

- 6-kant Abstandsbolzen mit M3 Innen-/Außengewinde
- Schlüsselweite (SW) 5,5
- Außengewinde mit Hinterstich nach DIN76
(kein Buchstabe „H“ in der Art.-Nr. bedeutet "ohne Hinterstich")
- Material: Messing vernickelt

Abmessungen

► Einheit = mm



Art.-Nr.	L (mm)	B (mm)	C (mm)
106 13 05 HB5	5,0	5,0	3,0
106 13 05 H	5,0	8,0	3,0
106 13 05 HB6	5,0	6,0	3,0
106 13 06 HB6	6,0	6,0	3,0
106 13 06 H	6,0	8,0	3,0
106 13 07 H	7,0	8,0	4,0
106 13 08 HB6	8,0	6,0	5,0
106 13 08 HB7	8,0	7,0	5,0
106 13 08 H	8,0	8,0	5,0
106 13 08,5 HB6	8,5	6,0	5,0
106 13 09 HB4	9,0	4,0	5,0
106 13 09 H	9,0	8,0	6,0
106 13 10 HB6	10,0	6,0	6,0
106 13 10 H	10,0	8,0	6,0
106 13 11 HB6	11,0	6,0	6,0
106 13 11 H	11,0	8,0	6,0
106 13 12 HB4	12,0	4,0	6,0
106 13 12 HB6	12,0	6,0	6,0
106 13 12 H	12,0	8,0	6,0
106 13 13 H	13,0	8,0	6,0
106 13 13,5 HB4	13,5	4,0	6,0
106 13 14 HB4	14,0	4,0	6,0
106 13 14 HB6	14,0	6,0	6,0
106 13 14 H	14,0	8,0	6,0
106 13 15 HB6	15,0	6,0	6,0
106 13 15 H	15,0	8,0	6,0

Art.-Nr.	L (mm)	B (mm)	C (mm)
106 13 16 HB6	16,0	6,0	7,0
106 13 17 H	17,0	8,0	6,0
106 13 18 HB6	18,0	6,0	6,0
106 13 18 H	18,0	8,0	6,0
106 13 19 H	19,0	8,0	6,0
106 13 20 H	20,0	8,0	6,0
106 13 21 H	21,0	8,0	6,0
106 13 22 H	22,0	8,0	6,0
106 13 24 H	24,0	8,0	6,0
106 13 25 HB6	25,0	6,0	6,0
106 13 25 H	25,0	8,0	6,0
106 13 28 H	28,0	8,0	6,0
106 13 29 H	29,0	6,0	6,0
106 13 30 H	30,0	6,0	6,0
106 13 30 HB8	30,0	8,0	6,0
106 13 35 H	35,0	6,0	6,0
106 13 40 H	40,0	6,0	6,0
106 13 40 HB8	40,0	8,0	8,0
106 13 44 H	44,0	6,0	6,0
106 13 45 H	45,0	6,0	6,0
106 13 50 H	50,0	6,0	6,0
106 13 55 H	55,0	8,0	6,0
106 13 60 H	60,0	6,0	6,0
106 13 65 H	65,0	6,0	6,0
106 13 75 H	75,0	6,0	6,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0



THORA
elektronik

www.thora.com