

ABS-IA-M4 - SW7 Abstandsbolzen




Merkmale

- 6-kant Abstandsbolzen mit M4 Innen-/Außengewinde
- Schlüsselweite (SW) 7
- Außengewinde mit Hinterstich nach DIN76
(kein Buchstabe "H" in der Art.-Nr. bedeutet "ohne Hinterstich")
- Material: Stahl verzinkt

Abmessungen

► Einheit = mm



Art.-Nr.	L (mm)	B (mm)	C (mm)
107 04 08 HB5	8,0	5,0	5,0
107 04 08 H	8,0	8,0	6,0
107 04 09 H	9,0	8,0	6,0
107 04 10 H	10,0	8,0	6,0
107 04 12 H	12,0	8,0	7,0
107 04 13 H	13,0	8,0	8,0
107 04 14 H	14,0	8,0	8,0
107 04 15 H	15,0	8,0	8,0
107 04 16 H	16,0	8,0	8,0
107 04 17 H	17,0	8,0	8,0
107 04 18 H	18,0	8,0	9,0
107 04 20 H	20,0	8,0	8,0
107 04 22 H	22,0	8,0	8,0
107 04 24 H	24,0	8,0	8,0
107 04 25 H	25,0	8,0	8,0
107 04 27 H	27,0	8,0	8,0
107 04 29 H	29,0	8,0	8,0
107 04 30 H	30,0	8,0	8,0
107 04 32 H	32,0	8,0	8,0
107 04 32,5 HB8	32,5	8,0	8,0
107 04 33 H	33,0	8,0	8,0
107 04 34 H	34,0	8,0	9,0
107 04 35 HB5	35,0	5,0	8,0

Art.-Nr.	L (mm)	B (mm)	C (mm)
107 04 35 H	35,0	8,0	9,0
107 04 35 HB10	35,0	10,0	8,0
107 04 38 H	38,0	8,0	8,0
107 04 40 H	40,0	8,0	8,0
107 04 42 H	42,0	8,0	8,0
107 04 43 H	43,0	8,0	10,0
107 04 44 H	44,0	8,0	10,0
107 04 45 H	45,0	8,0	8,0
107 04 46 H	46,0	8,0	8,0
107 04 48 H	48,0	8,0	8,0
107 04 50 H	50,0	8,0	8,0
107 04 54 H	54,0	8,0	8,0
107 04 55 H	55,0	8,0	8,0
107 04 60 H	60,0	8,0	8,0
107 04 65 H	65,0	8,0	8,0
107 04 67 H	67,0	8,0	8,0
107 04 70 H	70,0	8,0	8,0
107 04 75 H	75,0	8,0	6,0
107 04 80 H	80,0	8,0	6,0
107 04 92 H	92,0	8,0	8,0
107 04 95 H	95,0	8,0	6,0
107 04 100 H	100,0	8,0	6,0
107 04 105 H	105,0	10,0	10,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0



THORA
elektronik

www.thora.com