


ABS-IA-M4 - SW8 Abstandsbolzen




Merkmale

- 6-kant Abstandsbolzen mit M4 Innen-/Außengewinde
- Schlüsselweite (SW) 8
- Außengewinde mit Hinterstich nach DIN76
(kein Buchstabe "H" in der Art.-Nr. bedeutet "ohne Hinterstich")
- Material: Stahl glanzverzinkt

Abmessungen

► Einheit = mm



Art.-Nr.	L (mm)	B (mm)	C (mm)
108 04 08 H	8,0	8,0	6,0
108 04 10 HB5	10,0	5,0	6,0
108 04 10 H	10,0	8,0	6,0
108 04 12 H	12,0	8,0	8,0
108 04 13 H	13,0	8,0	8,0
108 04 14 H	14,0	8,0	8,0
108 04 15 H	15,0	8,0	8,0
108 04 17 H	17,0	8,0	8,0
108 04 18 H	18,0	8,0	8,0
108 04 20 H	20,0	8,0	8,0
108 04 22 H	22,0	8,0	8,0
108 04 24 H	24,0	8,0	8,0
108 04 25 H	25,0	8,0	8,0
108 04 27 H	27,0	8,0	8,0
108 04 28 H	28,0	8,0	8,0
108 04 30 H	30,0	8,0	8,0
108 04 31 H	31,0	8,0	8,0
108 04 35 HB6,5	35,0	6,5	8,0

Art.-Nr.	L (mm)	B (mm)	C (mm)
108 04 35 H	35,0	8,0	8,0
108 04 36 H	36,0	8,0	8,0
108 04 38 H	38,0	8,0	10,0
108 04 40 H	40,0	8,0	8,0
108 04 44 H	44,0	8,0	8,0
108 04 45 H	45,0	8,0	8,0
108 04 50 H	50,0	8,0	8,0
108 04 51 H	51,0	8,0	8,0
108 04 55 H	55,0	8,0	8,0
108 04 60 H	60,0	8,0	8,0
108 04 65 H	65,0	8,0	8,0
108 04 70 H	70,0	8,0	8,0
108 04 75 H	75,0	8,0	8,0
108 04 80 H	80,0	8,0	8,0
108 04 90 H	90,0	8,0	8,0
108 04 92 H	92,0	8,0	8,0
108 04 95 H	95,0	8,0	8,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0



THORA
elektronik

www.thora.com