

ABS-IA-M5 - SW8 Abstandsbolzen




Merkmale

- 6-kant Abstandsbolzen mit M5 Innen-/Außengewinde
- Schlüsselweite (SW) 8
- Außengewinde mit Hinterstich nach DIN76
(kein Buchstabe "H" in der Art.-Nr. bedeutet "ohne Hinterstich")
- Material: Stahl verzinkt

Abmessungen

► Einheit = mm



Art.-Nr.	L (mm)	B (mm)	C (mm)
108 05 10 HB6	10,0	6,0	6,0
108 05 10 H	10,0	10,0	6,0
108 05 12 H	12,0	10,0	7,0
108 05 13	13,0	8,0	10,0
108 05 15 H	15,0	10,0	10,0
108 05 16 H	16,0	10,0	10,0
108 05 17 H	17,0	10,0	10,0
108 05 18 H	18,0	10,0	10,0
108 05 20 H	20,0	10,0	10,0
108 05 22 H	22,0	10,0	10,0
108 05 23 H	23,0	10,0	10,0
108 05 25 H	25,0	10,0	10,0
108 05 27 H	27,0	10,0	10,0
108 05 30 H	30,0	10,0	10,0
108 05 32 H	32,0	10,0	10,0
108 05 35 H	35,0	10,0	10,0

Art.-Nr.	L (mm)	B (mm)	C (mm)
108 05 36 H	36,0	10,0	10,0
108 05 40 H	40,0	10,0	10,0
108 05 45 H	45,0	10,0	10,0
108 05 47 H	47,0	10,0	10,0
108 05 50 H	50,0	10,0	10,0
108 05 55 HB8	55,0	8,0	10,0
108 05 55 H	55,0	10,0	10,0
108 05 60 H	60,0	10,0	10,0
108 05 70 H	70,0	10,0	10,0
108 05 71 HB8	71,0	8,0	10,0
108 05 75 H	75,0	10,0	10,0
108 05 80 H	80,0	10,0	10,0
108 05 90 HB8	90,0	8,0	10,0
108 05 90 H	90,0	10,0	8,0
108 05 95 H	95,0	10,0	10,0
108 05 100 H	100,0	10,0	10,0

Weitere Abmessungen und Größen auf Anfrage, Tel.: 09852 61079-0

